

Data Preprocessing and Feature Engineering for ML

Prepare features that models can learn from. Imputation strategies, outlier handling, encoding categorical variables (one-hot, ordinal, target encoding), scaling (standard, min-max, robust), transformations (log, Box-Cox/Yeo-Johnson), binning, interactions and polynomial features, date and text features, and feature selection, all inside leak-free pipelines.

● ML class 6

✦ scikit-learn 1.7+

Intermediate

🕒 120 min

By the end of this lesson you can

- Impute missing values with simple, group-aware and model-based strategies and add missing indicators
- Encode nominal and ordinal categories correctly, including high-cardinality columns
- Choose a scaler and know which algorithms need scaling
- Engineer features from numbers, dates, text and domain knowledge
- Select features with filter, wrapper and embedded methods without leaking test data

Datasets used

`hr_employees.csv``house_prices.csv`

Why preprocessing matters

Algorithms only see numbers. How you represent the data often matters more than which algorithm you choose ("better data beats fancier models").

Preprocessing toolbox

Missing values

SimpleImputer, KNNImputer, IterativeImputer, missing indicators

Outliers

Cap (winsorise), log transform, robust scaler, or keep

Categories

One-hot, ordinal, target encoding, frequency encoding

Scaling

Standard, min-max, robust

Transformations

log, Box-Cox / Yeo-Johnson, binning, polynomial

New features

Ratios, dates, text, aggregates, domain rules

The preprocessing toolbox, applied inside a pipeline.

Missing values

Python

```
import pandas as pd, numpy as np
from sklearn.impute import SimpleImputer, KNNImputer
from sklearn.experimental import enable_iterative_imputer # noqa: F401
from sklearn.impute import IterativeImputer
h = pd.read_csv("house_prices.csv")
num = h[["area_sqft", "bedrooms", "bathrooms", "age_years", "price_lakh"]]
mask = num.area_sqft.isna(); print("missing area:", mask.sum())
for name, imp in [("median", SimpleImputer(strategy="median")), ("KNN (5 neighbours)",
KNNImputer(n_neighbors=5)), ("iterative (regression)", IterativeImputer(random_state=0))]:
    filled = pd.DataFrame(imp.fit_transform(num), columns=num.columns)
    print(f"{name:24s} imputed areas: mean {filled.loc[mask, 'area_sqft'].mean():7.0f}, sd
{filled.loc[mask, 'area_sqft'].std():6.0f}")
print("SimpleImputer(add_indicator=True) adds a column:", SimpleImputer(strategy="median",
add_indicator=True).fit(num[["area_sqft"]]).get_feature_names_out().tolist())
```

OUTPUT

missing area: 25

median	imputed areas: mean	1240,	sd	0
KNN (5 neighbours)	imputed areas: mean	1396,	sd	294
iterative (regression)	imputed areas: mean	1384,	sd	310

SimpleImputer(add_indicator=True) adds a column: ['area_sqft', 'missingindicator_area_sqft']

The median fills every gap with one value (sd 0); KNN and iterative imputers use the other columns (bedrooms, price), so they produce realistic, varied values. In real projects compare strategies with cross-validation, and never use the target to impute features at prediction time.

Encoding categorical variables

Python

```
from sklearn.preprocessing import OneHotEncoder, OrdinalEncoder, TargetEncoder
hr = pd.read_csv("hr_employees.csv")
print(hr.education.unique().tolist(), hr.department.nunique(), "departments |",
hr.job_title.nunique(), "job titles")
oh = OneHotEncoder(handle_unknown="ignore", sparse_output=False).fit(hr[["department"]])
print("one-hot:", oh.get_feature_names_out().tolist())
order = ["Diploma", "Bachelor's", "Master's", "PhD"]
present = [e for e in order[0] if e in set(hr.education)]
oe = OrdinalEncoder(categories=[present]).fit(hr[["education"]])
print("ordinal:", dict(zip(present, oe.transform(pd.DataFrame({"education":
present})).ravel()))))
y = (hr.attrition == "Yes").astype(int)
te = TargetEncoder(target_type="binary", random_state=0).fit(hr[["job_title"]], y)
print("target encoding (smoothed attrition rate per job title, first 4):",
dict(zip(te.categories_[0][:4], te.encodings_[0][:4].round(3))))
print("frequency encoding:",
hr.job_title.map(hr.job_title.value_counts(normalize=True)).round(3).head(3).tolist())
```

OUTPUT

```
["Bachelor's", "Master's", 'Diploma', 'PhD'] 6 departments | 18 job titles
one-hot: ['department_Finance', 'department_HR', 'department_IT',
'department_Operations', 'department_R&D', 'department_Sales']
ordinal: {'Diploma': np.float64(0.0), "Bachelor's": np.float64(1.0), "Master's":
np.float64(2.0), 'PhD': np.float64(3.0)}
target encoding (smoothed attrition rate per job title, first 4): {'Accountant':
np.float64(0.256), 'Analyst': np.float64(0.28), 'Data Scientist': np.float64(0.247),
'Developer': np.float64(0.295)}
frequency encoding: [0.049, 0.063, 0.063]
```

Encoding	For	Notes
One-hot	Nominal, few categories	One column per category; <code>handle_unknown="ignore"</code> ; <code>drop="first"</code> for linear models if needed
Ordinal	Ordered categories (education, size S/M/L)	Give the order explicitly
Target encoding	High-cardinality nominal (job title, city, merchant)	Uses the target: must be cross-fitted (sklearn's <code>TargetEncoder</code> does this)
Frequency / count	High cardinality	Simple, leak-free
Hashing, embeddings	Very high cardinality (IDs, text)	Fixed size; embeddings in deep learning

WATCH OUT Label encoding nominal data

Mapping cities to 0, 1, 2... tells linear models and KNN that "Pune (2) > Delhi (1)", a false order. Use one-hot encoding for nominal variables (tree models tolerate ordinal codes better).

Scaling

Python

```
from sklearn.preprocessing import StandardScaler, MinMaxScaler, RobustScaler
inc = hr[["monthly_income"]]
out = pd.DataFrame({"raw": inc.monthly_income})
for name, sc in [("standard", StandardScaler()), ("minmax", MinMaxScaler()), ("robust", RobustScaler())]:
    out[name] = sc.fit_transform(inc).ravel()
print(out.describe().loc[["mean", "std", "min", "50%", "max"]].round(2))
```


OUTPUT

	raw	standard	minmax	robust
mean	82610.67	-0.00	0.24	0.18
std	31145.80	1.00	0.17	0.71
min	39167.00	-1.40	0.00	-0.81
50%	74708.50	-0.25	0.20	0.00
max	218417.00	4.36	1.00	3.28

Scaler	Result	Use
StandardScaler	mean 0, sd 1	Default for linear models, SVM, PCA, neural networks
MinMaxScaler	range 0–1	Bounded inputs (neural networks, images)
RobustScaler	median 0, IQR 1	Data with outliers

Needs scaling: KNN, K-means, SVM, PCA, regularised linear/logistic regression, neural networks, gradient descent. **Does not:** decision trees, random forests, gradient boosting (they split on thresholds).

Transformations



Log and Yeo-Johnson transforms make right-skewed income closer to symmetric.

Log transforms help linear models with multiplicative effects (prices, incomes) and can be applied to the **target** too (`TransformedTargetRegressor`). Binning (`KBinsDiscretizer` , `pd.cut`) trades detail for robustness and interpretability.

Feature engineering

Good features encode domain knowledge the algorithm cannot easily find.

Python

```
hr["hire_date"] = pd.to_datetime(hr.hire_date)
fe = pd.DataFrame({
    "income_per_year_tenure": hr.monthly_income / (hr.years_at_company + 1),      # ratio
    "is_long_commute": (hr.distance_from_home_km > 20).astype(int),              #
    threshold from domain knowledge
    "overtime_x_low_sat": ((hr.overtime == "Yes") & (hr.job_satisfaction ≤
2)).astype(int),      # interaction
    "hire_month": hr.hire_date.dt.month, "hired_in_q4":
hr.hire_date.dt.quarter.eq(4).astype(int),      # date parts
    "income_vs_dept_median": hr.monthly_income /
hr.groupby("department").monthly_income.transform("median"),      # group-relative
    "title_is_manager": hr.job_title.str.contains("Manager").astype(int),      # text
    pattern
})
fe["left"] = (hr.attrition == "Yes").astype(int)
print(fe.corr()["left"].drop("left").round(3).sort_values())
print(fe.groupby("overtime_x_low_sat").left.mean().round(3).to_dict())
```

OUTPUT

```
income_vs_dept_median    -0.109
title_is_manager          -0.048
hire_month                0.038
hired_in_q4              0.043
income_per_year_tenure    0.057
is_long_commute           0.094
overtime_x_low_sat        0.165
Name: left, dtype: float64
{0: 0.229, 1: 0.43}
```

Source	Feature ideas
Numbers	Ratios, differences, logs, bins, polynomial and interaction terms
Dates	Day of week, month, holiday flags, days since last event, tenure, seasonality (sin/cos)
Transactions	Recency, frequency, monetary (RFM), averages over 7/30/90 days, trends
Text	Length, keyword flags, TF-IDF, embeddings (lesson 25 and GenAI track)
Geography	Distance to centre/store, region aggregates
Groups	Value relative to group mean/median (income vs department)

Python

```
from sklearn.preprocessing import PolynomialFeatures
pf = PolynomialFeatures(degree=2, include_bias=False).fit(pd.DataFrame({"area": [1], "age": [1]}))
print(pf.get_feature_names_out().tolist())
```

OUTPUT

```
['area', 'age', 'area^2', 'area age', 'age^2']
```

Feature selection

More features are not always better: irrelevant ones add noise, cost and overfitting.

Python

```
from sklearn.feature_selection import mutual_info_classif, SelectKBest, RFE
from sklearn.linear_model import LogisticRegression
from sklearn.ensemble import RandomForestClassifier
Xn = pd.get_dummies(hr[["age", "monthly_income", "years_at_company", "job_satisfaction",
"distance_from_home_km", "performance_rating", "overtime", "department"]],
drop_first=True).astype(float)
mi = pd.Series(mutual_info_classif(Xn, y, random_state=0),
index=Xn.columns).sort_values(ascending=False)
print("filter (mutual information):", mi.round(3).head(5).to_dict())
rfe = RFE(LogisticRegression(max_iter=2000),
n_features_to_select=4).fit(StandardScaler().fit_transform(Xn), y)
print("wrapper (RFE, logistic):", Xn.columns[rfe.support_].tolist())
rf = RandomForestClassifier(300, random_state=0, min_samples_leaf=5).fit(Xn, y)
print("embedded (random forest importance):", pd.Series(rf.feature_importances_,
Xn.columns).sort_values(ascending=False).round(3).head(5).to_dict())
```

OUTPUT

```
filter (mutual information): {'years_at_company': 0.025, 'job_satisfaction': 0.019,
'department_HR': 0.017, 'monthly_income': 0.009, 'overtime_Yes': 0.007}
wrapper (RFE, logistic): ['years_at_company', 'job_satisfaction',
'distance_from_home_km', 'overtime_Yes']
embedded (random forest importance): {'monthly_income': 0.242,
'distance_from_home_km': 0.18, 'age': 0.155, 'years_at_company': 0.117,
'job_satisfaction': 0.108}
```

The three methods disagree. That is normal: they measure different things. Random-forest (impurity) importances also favour continuous features with many distinct values, so check them with permutation importance (lesson 27).

Method	How	Pros / cons
Filter	Score each feature (correlation, chi-square, mutual information)	Fast; ignores interactions
Wrapper	Search subsets with a model (RFE, forward selection)	Strong; slow, risk of overfitting
Embedded	Selection during training (Lasso L1, tree importances)	Efficient; model-specific

Do feature selection **inside** cross-validation (in the pipeline) so the test data never influences which features are chosen.

Putting it together: a leak-free pipeline

Python

```
from sklearn.compose import ColumnTransformer
from sklearn.pipeline import Pipeline, make_pipeline
from sklearn.model_selection import cross_val_score
X = hr.drop(columns=["emp_id", "attrition", "hire_date"])
pre = ColumnTransformer([
    ("num", make_pipeline(SimpleImputer(strategy="median"), StandardScaler()), ["age",
"years_at_company", "monthly_income", "job_satisfaction", "distance_from_home_km",
"performance_rating"]),
    ("ord", OrdinalEncoder(categories=[present]), ["education"]),
    ("ohe", OneHotEncoder(handle_unknown="ignore"), ["gender", "department", "overtime",
"city"]),
    ("te", TargetEncoder(target_type="binary", random_state=0), ["job_title"]),
])
pipe = Pipeline([("pre", pre), ("sel", SelectKBest(mutual_info_classif, k=12)), ("model",
LogisticRegression(max_iter=2000))])
scores = cross_val_score(pipe, X, y, cv=5, scoring="roc_auc")
print(f"5-fold ROC-AUC {scores.mean():.3f} ± {scores.std():.3f}")
```

OUTPUT

5-fold ROC-AUC 0.661 ± 0.013

Summary

KEY TAKEAWAYS

- Impute with medians/modes, KNN or iterative imputers, and add missing-value indicators when missingness carries information.
- One-hot for nominal, ordinal encoding with an explicit order, target or frequency encoding for high-cardinality columns.
- Scale for distance- and gradient-based models (standard, min-max, robust); trees do not need scaling.
- Transform skewed variables (log, Yeo-Johnson); engineer ratios, interactions, date and group-relative features from domain knowledge.
- Select features with filter, wrapper or embedded methods, always inside the cross-validated pipeline.

Quick quiz

6 questions · tap an answer to check it

1. Which encoding suits "education level" (Diploma < Bachelor's < Master's < PhD)?

A Ordinal encoding with the order given explicitly

B One-hot only

C Target encoding only

D Leave as text

Answer: A. The categories have a natural order.

2. Which algorithm does NOT need feature scaling?

A KNN

B SVM

C Random forest

D K-means

Answer: C. Trees split on thresholds, unaffected by scale.

3. Why must target encoding be cross-fitted?

A Using a row's own target to encode it leaks the answer and overfits

B It is slow otherwise

C It needs scaling

D It only works on numbers

Answer: A. sklearn's TargetEncoder handles this internally.

4. What does RobustScaler use?

A Mean and standard deviation

B Median and interquartile range

C Min and max

D Logarithms

Answer: B. Robust to outliers.

5. Where should feature selection happen?

- A On the full dataset before splitting
- B Inside the pipeline, within cross-validation on training data**
- C On the test set
- D After deployment

Answer: B. Otherwise test information leaks into the choice.

6. Which is an interaction feature?

- A monthly_income
- B overtime AND low job satisfaction**
- C $\log(\text{income})$
- D hire_month

Answer: B. It combines two features.

EXERCISE Practice (house_prices.csv)

(1) Engineer `price_per_sqft`, `rooms = bedrooms + bathrooms`, `is_new = age_years ≤ 5`. Which correlate most with price? (Careful: `price_per_sqft` uses the target, so it cannot be a feature!) (2) Build a pipeline with KNN imputation, one-hot city, standard scaling and Ridge regression; report 5-fold R^2 . (3) Try a log-transformed target with `TransformedTargetRegressor`.

Show solution (worked answer)

Python

```
from sklearn.linear_model import Ridge
from sklearn.compose import TransformedTargetRegressor
h["rooms"] = h.bedrooms + h.bathrooms; h["is_new"] = (h.age_years ≤ 5).astype(int)
Xh = h.drop(columns=["house_id", "price_lakh"]); yh = h.price_lakh
pre_h = ColumnTransformer([("num", make_pipeline(KNNImputer(), StandardScaler()),
["area_sqft", "bedrooms", "bathrooms", "age_years", "distance_to_center_km",
"parking", "rooms", "is_new"]), ("cat", OneHotEncoder(handle_unknown="ignore"),
["city"])]])
print(cross_val_score(Pipeline([("p", pre_h), ("m", Ridge())]), Xh, yh, cv=5,
scoring="r2").mean())
print(cross_val_score(Pipeline([("p", pre_h), ("m",
TransformedTargetRegressor(Ridge(), func=np.log1p, inverse_func=np.expm1)])), Xh, yh,
cv=5, scoring="r2").mean())
```

INTERVIEW CORNER Questions you may be asked

Q: How do you handle categorical variables with 1,000 levels? Target encoding (cross-fitted), frequency encoding, grouping rare levels into "Other", hashing, or learned embeddings; tree-based libraries like CatBoost handle them natively.

Q: Normalisation vs standardisation? Normalisation (min-max) rescales to 0–1; standardisation centres to mean 0 and sd 1. Use standardisation by default; min-max for bounded inputs.

Q: Give an example of a feature you engineered that helped. Use STAR: e.g. "days since last purchase" and "spend in the last 30 days vs previous 30" for churn, which raised recall in the top decile from X to Y.

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.